

Two-way VHF radiotelephone

JHS-207



- Floating GMDSS two-way VHF radiotelephone
- Access to all maritime VHF channels with rechargeable battery
- Preset emergency mode when connected to primary battery
- Excellent microphone noise cancelling



Category

All vessel types



Deepsea



Workboats



Fishing



Yachting

Features |

The JHS-207 two-way VHF radiotelephone is an innovated “two-in-one” radio, which gives the user the opportunity to access both standard GMDSS channels and all maritime VHF channels. The floating VHF radiotelephone equipment meets the GMDSS mounting carriage requirements.

- Excellent sound quality under all conditions
- Intuitive and easy-to-use design, lightweight and compact
- Depending on the installed battery, automatically switch to emergency mode and regular mode
- Large-capacity battery pack enables long-time operation of 12 hours
- Up to 57 channels can be used in regular mode

Intuitive design |

The JHS-207 has an intuitive and easy-to-use compact design which only weighs 0.3 kg including battery pack. The small and compact two-positioning charger is easy to install and allows the user to access vital information on the display while charging. The lightweight design will help to prevent fatigue during prolonged use.

Floating |

The VHF has a watertight facility socket and is the first portable two-way VHF radiotelephone that floats without a buoyancy cover. Additionally a range of waterproof accessories are available to complete the package.



Emergency mode |

The JHS-207 two-way VHF radiotelephone has the ultimate functional design. Every detail has been developed based on user functionality, both in an emergency situation (emergency battery) and in general on board communications (rechargeable battery). When connecting the emergency battery, the radio is automatically in preset emergency mode. Only emergency required features are accessible, thus reducing critical manual radio adjustment time for the user.

Battery |

The large-capacity battery pack enables long-time operation of 12 hours¹ so you can use it with confidence for a prolonged time even in an emergency.

¹Ratio during sending 10: receiving 10: standby: 80



Full VHF channels |

Up to 57 channels can be used in regular mode and 54 channels equivalent to the two-way VHF radiotelephone device can be used.

Microphone |

The JHS-207 two-way VHF radiotelephone has excellent microphone noise cancelling, which can be convenient during noisy onboard daily operations. The VHF can also be connected to an IP67 speaker microphone or a headset with a PTT-module.




Tech Specs |

Two-way VHF radiotelephone RoHS

JHS-207 Weight Radio with emergency battery: Approx. 0.3 kg (0.66 lbs)

Weight Radio with rechargeable battery: Approx. 0.295 kg (0.65 lbs)



In the box

JHS-207M

- Two-way VHF radiotelephone JHS-207
- Emergency battery NBB-789 (nonrechargeable)
- Rechargeable battery NBB-748
- Battery charger NJD101037
- Power supply NJD101038
- Instruction manual

Optional

- Speaker microphone 7UMJD0021
- Push-to-talk (PTT) module NJD19601
- Headset NJD103000
- Carry case with strap 7ZZJD0128
- Multi battery charger (kit) NZB-191
- Earphone mic 7UMJD0022

Specifications |

Technical		Emergency battery (non chargeable)	Rechargeable battery
Frequency range		154.000-157.425 MHz	154.000-161.875 MHz
Channel spacing		25 KHz	25 KHz
Operating temperature range		-20 to +55 °C	-20 to +55 °C
Battery operating time		12 h (10:10:80)	Typ. 12 h (10:10:80) medium power
Size (WHD)		64 mm×163 mm×40 mm (Depth with belt clip 47 mm)	64 mm×163 mm×40 mm (Depth with belt clip 47 mm)
Operating channels		21 channels	Up to 57 channels
Weight		Approx. 0.3 kg	Approx. 0.295 kg
Receiver			
Maximum usable sensitivity		< 1 µV at 20 dB SINAD	< 1 µV at 20 dB SINAD
Adjacent channel selectivity		> 70 dB	> 70 dB
Blocking		> 90 dB	> 90 dB
Spurious response		> 70 dB	> 70 dB
Harmonic distortion		< 5 %	< 5 %
Intermodulation rejection		> 68 dB	> 68 dB
Channel monitoring		DW	DW/TW/Scan
Transmitter			
Transmitter output power (fully charged battery)		Lo: 1 W, Hi: 2 W	Lo: 1 W, Mid: 2 W (default), Hi: 4 W
Harmonics and spurious		< 0.25 µW	< 0.25 µW
Frequency error		Within ±1.5 kHz	Within ±1.5 kHz
Adjacent channel power		< -70 dBc	< -70 dBc
Approval standards			
EMC / Environmental		IEC 60945 / EN 301 843-2	IEC 60945 / EN 301 843-2
VHF		IEC 61097-12 / EN 300 225	EN 301 178
Charger			
Operating power source		100-240 VAC (with power supply)	
Mounting		Wall and table mountable	
Size (WHD)		92 mm×74.5 mm×114.2 mm	
Battery		Emergency battery (non chargeable)	Rechargeable battery
Chemical system		Lithium/Iron Disulfide (Li/FeS2) Battery	Lithium Polymer Battery
Voltage		6V Nominal	7.4V Nominal
Capacity		3000 mAh	1550 mAh



ALPHATRON
Marine



www.jrc-world.com

Centers of Excellence

JRC (Japan Radio Co.,Ltd)
1-7-32 Tatsumi, Koto-ku
Tokyo 135-0053
Japan
+81 3 5534 7800

JRC Shanghai Co.,Ltd.
Floor 9-A Building C2
Shanghai International Trade Center
1599 New Jinqiao Road
Pudong, Shanghai, China 201206
+86 21 2024 0607

JRC/ProNav AS
Hovlandsveien 52
4374 Egersund
Norway
+47 5146 4300

JRC/Alphatron Marine B.V.
Schaardijk 23
3063 NH Rotterdam
The Netherlands
+31 10 453 4000

JRC South East Asia
59 S, Tuas South Avenue
Ho Lee Industrial Development
637418 Singapore
Singapore
+65 6863 0335

JRC Americas
1205 Butler Road
TX 77573 Houston
United States of America
+1 281 271 4600